

the scheduled process, the maintenance of which vacuum is critical to the adequacy of the scheduled process.

(v) *Vents* means openings through the retort shell, controlled by gate, plug cock, or other adequate valves used for the elimination of air during the venting period.

(w) *Water activity* (a_w) is a measure of the free moisture in a product and is the quotient of the water vapor pressure of the substance divided by the vapor pressure of pure water at the same temperature.

§ 113.5 Current good manufacturing practice.

The criteria in §§ 113.10, 113.40, 113.60, 113.81, 113.83, 113.87, 113.89, and 113.100 shall apply in determining whether the facilities, methods, practices, and controls used by the commercial processor in the manufacture, processing, or packing of low-acid foods in hermetically sealed containers are operated or administered in a manner adequate to protect the public health.

§ 113.10 Personnel.

The operators of processing systems, retorts, aseptic processing and packaging systems and product formulating systems (including systems wherein water activity is used in conjunction with thermal processing) and container closure inspectors shall be under the operating supervision of a person who has attended a school approved by the Commissioner for giving instruction appropriate to the preservation technology involved and who has been identified by that school as having satisfactorily completed the prescribed course of instruction. This person shall supervise only in those areas for which a school approved by the Commissioner identifies the person as having satisfactorily completed training.

Subpart B [Reserved]

Subpart C—Equipment

§ 113.40 Equipment and procedures.

(a) *Equipment and procedures for pressure processing in steam in still retorts—*
(1) *Indicating mercury-in-glass thermometer.* Each retort shall be equipped with at least one mercury-in-glass ther-

момeter whose divisions are easily readable to 1 °F and whose temperature range does not exceed 17 °F per inch of graduated scale. Thermometers shall be tested for accuracy against a known accurate standard thermometer upon installation and at least once a year thereafter, or more frequently if necessary, to ensure their accuracy. Records of thermometer accuracy checks that specify date, standard used, method used, and person performing the test should be maintained. Each thermometer should have a tag, seal, or other means of identity that includes the date on which it was last tested for accuracy. A thermometer that has a divided mercury column or that cannot be adjusted to the standard shall be repaired or replaced before further use of the retort. Thermometers shall be installed where they can be accurately and easily read. Bulbs of indicating thermometers shall be installed either within the retort shell or in external wells attached to the retort. External wells or pipes shall be connected to the retort through at least a 3/4-inch diameter opening and equipped with a 1/16-inch or larger bleeder opening so located as to provide a full flow of steam past the length of the thermometer bulb. The bleeders for external wells shall emit steam continuously during the entire processing period. The mercury thermometer—not the recorder chart—shall be the reference instrument for indicating the processing temperature.

(2) *Temperature-recording device.* Each still retort shall have an accurate temperature-recording device. Graduations on the temperature-recording devices shall not exceed 2 °F within a range of 10 °F of the processing temperature. Each chart shall have a working scale of not more than 55 °F per inch within a range of 20 °F of the processing temperature. The temperature chart shall be adjusted to agree as nearly as possible with, but to be in no event higher than, the known accurate mercury-in-glass thermometer during the process time. A means of preventing unauthorized changes in adjustment shall be provided. A lock, or a notice from management posted at or near the recording device which provides a warning